



STRUCTURAL - UNIVERSAL & TAPER FLANGE BEAMS

Description	Depth of Section (D)	Flange Width (W)	Flange Thickness (f)	Web Thickness (w)	Weight
	mm	mm	mm	mm	kg/m
Standard lengths (mtrs) - 9, 10.5, 12, 13.5, 15, 16.5, 18.					
UNIVERSAL BEAMS					
150UB14.0	150	75	7	5	14
150UB18.0	155	75	9.5	6	18
180UB16.1	173	90	7	4.5	16.1
180UB18.1	175	90	8	5	18.1
180UB22.2	179	90	10	6	22.2
200UB18.2	198	99	7	4.5	18.2
200UB22.3	202	133	7	5	22.3
200UB25.4	203	133	7.8	5.8	25.4
200UB29.8	207	134	9.6	6.3	29.8
250UB25.7	248	134	8	5	25.7
250UB31.4	252	146	8.6	6.1	31.4
250UB37.3	256	146	10.9	6.4	37.3
310UB32.0	298	149	8	5.5	32
310UB40.4	304	165	10.2	6.1	40.4
310UB46.2	307	166	11.8	6.7	46.2
360UB44.7	352	171	9.7	6.9	44.7
360UB50.7	356	171	11.5	7.3	50.7
360UB56.7	359	172	13	8	56.7
410UB53.7	403	178	10.9	7.6	53.7
410UB59.7	406	178	12.8	7.8	59.7
460UB67.1	454	190	12.7	8.5	67.1
460UB74.6	457	190	14.5	9.1	74.6
460UB82.1	460	191	16	9.9	82.1
530UB82.0	528	209	13.2	9.6	82
530UB92.4	533	209	15.6	10.2	92.4
610UB101.0	602	228	14.8	10.6	101
610UB113.0	607	228	17.3	11.2	113
610UB125.0	610	229	19.6	11.9	125
TAPER FLANGE BEAMS					
100 x 45	100	45	6	4	7.2
125 x 65	125	65	8.5	5	13.1